

Clearwater DUO™

The Next Generation in Chlorinators

Let your chlorinator
do the hard work



The new Clearwater DUO combines the essentials of pool automation with a highly durable chlorine generator and sets a new level for chlorinators.

Using built-in WiFi to keep you connected with full control at your finger tips, thru to upgraded cell plates to ensure ultra long life.



DOWNLOAD
OR UPDATE

the iAqualink
app from



Clearwater DUO™



SMART TEMPERATURE SENSOR

Not only can you view realtime water temp but this smart sensor automatically regulates output in cold water thus preventing excessive wear and tear on your cell, helping to reduce costs



ULTRA LONG LIFE RP CELL

These upgraded automatic cleaning cell plates have an ultra long life, combined with smart tech in the chlorine production that will provide years of performance



VARIABLE SPEED PUMP CONTROL

Directly connect to your VS pump and reduce energy consumption (must be RS485 communication pump)



IAQUALINK ENABLED

iAquaLink puts full control at your fingertips anytime, anywhere (check for marked carton if WiFi enabled)



SALT OR MINERAL SWITCHER

Use normal pool salt or mineral salts to create chlorine and keep your pool water healthy and sanitised at all times



MULTI COLOUR LIGHT CONTROL

Control your pool light(s) directly from the chlorinator (or your smart phone with iAquaLink). Any single colour light or Zodiac/Jandy sequence multi colour light. Note this feature requires additional relay box to connect. Ask your poolcare professional for more information



UPGRADES FOR WATER CHEMISTRY CONTROL

For your pools pH and chlorine levels with optional upgrade kits available which includes premium grade sensors

| MODELS | Clearwater Duo® iQ Mid | Clearwater Duo® iQ Large |
|---|--|--------------------------|
| Recommended pool size '000L See graph for guidance | 75 | 100 |
| Nominal chlorine production | 25 g/h | 35 g/h |
| Operating mode(s) | Normal = adjustable by 10% increments from 0% - 100% Low Mode = adjustable range 0 to 30% Boost Mode = continuous 100% for 24hrs | |
| Equipment control | Filter pump: Any single speed pump or Zodiac® variable speed pump. Lights: Any single colour light or any Zodiac/Jandy sequence Multicolour light (note will require additional relay box part number WW000222) | |
| Salt level (recommended at 25°C) | 4000ppm | |
| Cell protection | Temperature sensor controls chlorine output in cold water conditions assisting to protect cell against excessive wear and tear | |
| Power supply | 197 W / 110-240 VAC / 50-60 Hz | |
| Dimensions | Power pack: H-370mm x W-320mm x D-100mm Cell: H-160mm x W-320mm x D-110mm | |
| Warranty | Power Pack and cell: 3 Years Probes, tubing and consumables etc: 1 year | |

WHAT SIZE CLEARWATER DUO™ CHLORINATOR DO YOU NEED?

